

MPN: RDL26U68BL

by Logon 19" 26U Rack Cabinet 600 x 800mm Data Line

Product Dimensions: W:600 x D:800 x H:1342mm

Free-standing rack cabinets offers the most ideal solutions at the offices and system rooms in the areas of cabling and server installations. The cabinets created in a highly strong and robust structure are unrivalled in their class thanks to their low costs, unique design of top class profile design and easy assembly features.



The Installation Rails of the cabinets are adjustable through the cabinet depth. These cabinet series offer user-friendly and time-saving solutions with the widest accessories range. Thanks to its Flatpack option, the cabinets take less space in the warehouse and transport and are cost-effective. With the specially designed structure, the cabinets can be assembled and unassembled easily. Simple tools will be enough to assemble the whole cabinet.

Cabling Managing Made Easier

The cabinets are designed to enable the integration of vertical cable manager module structurally. Thus, a bigger cable mass can be managed with these cable managers.

The bottom chassis has a wide cable entry. The rubber edged sliding cable entry module directs the mass cables. After the cables are directed inside the cabinet, the sliding part is closed and fixed. The rubber edges are closed without any damage to the cables and the dust proof structure is provided on the maximum level available. Thanks to the Tire-Up structured side bracket provided, it's extra advantageous to direct the cables upwards and downwards and to fix them in the exact position.

Secured Door

The front door modules with horizontally split glass doors consist of decorative metal frame on both left and right. The front doors with full size, break-resistant, tempered, anti-static 4mm smoke colored glass are lockable by the handle-locking mechanism.

The other sides are strengthened with U and Y shaped lockable and interlockable special metal bars.

The rear door is solid metal and is easy to remove especially during relocation, installation and maintenance of the cabinet and system inside. The easily removable rear doors have the barrel-locking mechanism.

Easy Secure Access from All Sides

The cabinets have the maximum strength with the side brackets and extra cube omega support points.

The side panel of the cabinets are easily removable and have a barrel-locking system. The 42U and 46U high cabinets have vertically split side panels and it enables easy removal of the panels during installation and maintenance or when there is not enough space available.

- Glass Door
- Free-Standing
- RAL9005
- Cage nuts can be bought separate

Caractéristiques

Autres caractéristiques	Conformité aux standards industriels	IEC 60297-3-109, IEC 60297-3-100, IEC 61587-1.
	Dimensions (LxPxH)	600x800x1342 mm
Caractéristiques	Assemblage requis	Non
	Capacité de charge maximale	2000 kg
	Capacité du rack	26U
	Code (IP) Internationale Protection	IP20
	Conformité RoHS	Oui
	Construction de la porte arrière	Acier
	Construction de la porte avant	Verre/Acier
	Construction du panneau latéral	Acier
	Couleur du produit	Noir
	Forme de trou de montage	Carré
	Insonorisé	Non
	Matériel	Verre, Aluminium, Acier
	Montants avant	Réglable
	Panneaux latéraux amovibles	Oui
	Panneaux latéraux fournis	Oui
	Pieds réglables	Oui
	Point d'entrée du câble	Oui
	Porte arrière amovible	Oui
	Pré-assemblé	Oui
	Rails de montage réglables	Oui
	Rails de rack	Oui
	Roues castor	Non
	Style de la porte arrière	Aveugle
	Style de la porte avant	Porte en verre
	Style du panneau latéral	Aveugle
	Type	19" Freestanding Rack
	Type de refroidissement	Passif
	Type de trame	Closed
	Verrou à clé pour panneau latéral	Oui
	Verrou à clé pour porte arrière	Oui
	Verrou à clé pour porte avant	Oui
	Verrouillage des touches	Oui
	Vis inférieure de stabilisation	Oui
Poids et dimensions	Taille (impériale)	19 "
Vendor information	Brand Name	Lanview
	Warranty	5 Année (s)

Autres produits de cette série

Capacité du rack	Blanc	Noir
12U	RDL12U68WH	RDL12U68BL-PFD
16U	RDL16U68WH	RDL16U68BL
20U	RDL20U68WH	RDL20U68BL-TOP
22U	RDL22U68WH	RDL22U68BL
26U	RDL26U68WH	RDL26U68BL
32U	RDL32U68WH	RDL32U68BL
36U	RDLPCCAB36U	RDL36U68BL
42U	RDL42U68WH	RDL42U68BL-PER
46U	RDL46U68WH	RDL46U68BL-PF

Autres photos

