



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5070 12G VENTUS 2X OC
Modèle	G5070-12V2C
Processeur graphique	NVIDIA® GeForce RTX™ 5070
Cœurs	6144 unités
Mémoire	12 Go GDDR7
Bus Mémoire	192-bit
Fréquence du GPU	Performances extrêmes : 2557 MHz (MSI Center) Boost : 2542 MHz
Vitesse mémoire	28 Gb/s
Nombre d'écrans supportés	4
Technologie G-SYNC™	Oui
Résolution numérique maximum	7680 x 4320
Support du procédé HDCP	Oui
Bloc d'alimentation recommandé	650 watts
Connecteurs alimentation	1 x 16 broches
Sorties	3 x DisplayPort (v2.1b) 1 x HDMI™ (caractéristiques du HDMI™ 2.1b : jusqu'à 4K 480 Hz ou 8K 120 Hz avec DSC, Gaming VRR, HDR)
Version OpenGL	4.6
Dimensions	236 x 126 x 50 mm
Poids	774 g / 1149 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.




TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.