

# **Memory Module Specifications**

# KSM48R40BD4TMM-64HMR

64GB 2Rx4 8G x 80-Bit PC5-4800 CL40 Registered EC8 288-Pin DIMM

#### **DESCRIPTION**

Kingston's KSM48R40BD4TMM-64HMR is a 8G x 80-bit (64GB) DDR5-4800 CL40 SDRAM (Synchronous DRAM), 2Rx4, ECC, memory module, based on forty 4G x 4-bit FBGA components. The SPD is programmed to JEDEC standard latency DDR5-4800 timing of 40-39-39 at 1.1V. Each 288-pin DIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

## **FEATURES**

- Power Supply: VDD = 1.1V Typical
- VDDQ = 1.1V Typical
- VPP = 1.8V Typical
- VDDSPD = 1.8V to 2.0V
- · On-Die ECC
- x80 ECC (x40, 2 independent I/O sub channels)
- · 32 internal banks
- · Hard/Soft Post Package Repair
- · Sideband access with I3C/I2C
- PCB: Height 1.23" (31.25mm)
- · RoHS Compliant and Halogen-Free

### **SPECIFICATIONS**

CL(IDD)	40 cycles
Row Cycle Time (tRCmin)	48ns(min.)
Refresh to Active/Refresh Command Time (tRFCmin)	295ns(min.)
Row Active Time (tRASmin)	32ns(min.)
Row Precharge Time (tRPmin)	16ns(min.)
UL Rating	94 V - 0
Operating Temperature	0° C to +95° C
Storage Temperature	-55° C to +100° C

## **Module Assembly**

DRAM: HYNIX (M-Die)


RCD: Rambus PMIC: TI


SPD Hub: Montage


TS: Montage

Continued >>

## **MODULE DIMENSIONS**







The product images shown are for illustration purposes only and may not be an exact representation of the product. Kingston reserves the right to change any information at anytime without notice.

Revision No.	History	Release Date	Remark	Editor	Approved
Α	Initial Release	12/2/2022		Kirk F.	Henry N.
В	Change measurements (pg2)	4/24/2023		David Yen	Henry N.

<sup>\*</sup>Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change without notice. All information discussed herein is provided on an "as is" basis, without warranties of any kind.

Rev. B