



204 PIN DDR3 SODIMM

512Mx64 DDR3 SDRAM DIMM based on 256x8, 8Banks,
8K Refresh, 1.5V Synchronous DRAMs with SPD

MEM106004GBS

Description

The Hypertec OEM 4GB DDR3 SODIMM 256x8 memory module is organised as 512 Meg x 64 bits in a 204 pin memory module. The 4GB memory module uses 16 pieces 256M x 8 DDR3 SDRAMs. The x64 modules are ideal for use in high performance computer systems where increased memory density and fast access are required. The SPD is programmed to JEDEC standard latency and timing at 1.5V, this SODIMM uses gold edge contacts.

Features

- Programmable CAS Latency: 11, 9, 7
- 204-pin, small outline dual in-line memory module (SODIMM)
- Fast data transfer rates: PC3-12800, PC3-10600, PC3-8500
- 4GB (512 Meg x 64)
- VDD = VDDQ = +1.5V ± 0.075V
- VDDSPD = +3.0V to +3.6V
- Reset pin for improved system stability
- Nominal and dynamic on-die termination (ODT) for data, strobe and mask signals
- Dual Rank
- 8 internal device banks for concurrent operation
- Fixed burst length (BL) of 8 and burst chop (BC) of 4 via the mode register
- Adjustable data-output drive strength
- Serial presence-detect (SPD) EEPROM
- Gold edge contacts
- Lead-free and ROHS compliant
- Lifetime warranty