



204 PIN DDR3 SODIMM

256Mx64 DDR3 SDRAM DIMM based on 256x8, 8Banks,
8K Refresh, 1.35V Synchronous DRAMs with SPD

MEM128004GBS-LV

Description

The Hypertec OEM 4GB DDR3 SODIMM 256x8 memory module is organised as 256 Meg x 64 bits in a 204 pin memory module. The 4GB memory module uses 8 pieces 256M x 8 DDR3 SDRAMs. The x64 modules are ideal for use in high performance computer systems where increased memory density and fast access are required. The SPD is programmed to JEDEC standard latency and timing at 1.35V, this SODIMM uses gold edge contacts.

Features

- Programmable CAS Latency: 11, 9, 7
- 204-pin, small outline dual in-line memory module (SODIMM)
- Fast data transfer rates: PC3-12800, PC3-10600, PC3-8500 or PC3-6400
- 4GB (256 Meg x 64)
- $VDD = VDDQ = +1.35V \pm 0.075V$
- $VDDSPD = +3.0V$ to $+3.6V$
- Reset pin for improved system stability
- Nominal and dynamic on-die termination (ODT) for data, strobe and mask signals
- Single Rank
- 8 internal device banks for concurrent operation
- Fixed burst length (BL) of 8 and burst chop (BC) of 4 via the mode register
- Adjustable data-output drive strength
- Serial presence-detect (SPD) EEPROM
- Gold edge contacts
- Lead-free and ROHS compliant
- Lifetime warranty

PLEASE NOTE: The Hypertec OEM module defined in this specification is one of several configurations available under this part number. All configurations are compatible, however, the DRAM combination and/or memory module height may vary.