

MPN: PROHDMIHD3

ProFusion Pro HDMI Cable 3 Meter

High flexible jacket. HD 1080P. Support ARC, 3D, HDCP, CEC. 99,99% pure copper conductor.

- All HDMI resolutions up to 4K (4096x2160p @60Hz), including 3D video
- Support sample rate 4:4:4
- High Dynamic Range (HDR)
- Transfer speed 18 Gbit/s
- HDCP 2.2
- Supports Deep Color, up to 16-bits per channel, including x.v.Color standard
- Supports the 21:9 cinema aspect ratio
- Supports SA-CD, DVD-Audio, DTS-HD Master Audio, Dolby TrueHD, and other high definition audio standards
- Audio Return Channel
- Auto Lip Sync
- Supports up to 32 audio channels and a 1536 kHz audio sampling rate
- Dynamic sound synchronization
- Supports extended CEC (Consumer Electronics Control) commands and functions
- the HDMI Ethernet Channel, and the Audio Return Channel features
- Fully assembled with 19 pins connected
- High quality HDMI A connector, 15um gold min. in contact area for high reliability
- and professional use
- 99,9% pure copper wires for lossless picture transmission
- Triple shielded cable and extra shielding in the connector
- High Flexibility ensuring small bending radius



Caractéristiques

Features		
Canal de retour audio (ARC, Audio Return Channel)	Oui	
Canal Ethernet HDMI	Oui	
Compatibilité 3D	Oui	
Conformité RoHS	Oui	
Connecteur 1	HDMI Type A (Standard)	
Connecteur 2	HDMI Type A (Standard)	
Contacts du connecteur de placage	Or	
Couleur du produit	Noir	
Facteur de forme du connecteur 1	Droit	
Facteur de forme du connecteur 2	Droit	
Genre de connecteur 1	Mâle	
Genre de connecteur 2	Mâle	
HDCP	Oui	
Longueur de câble	3 m	

Features	Matière du câble	Cuivre
	Modes vidéo pris en charge	2160p
	Plage dynamique élevée 10 (HDR10)	Oui
	Plug and Play	Oui
	Prise en charge HDR	Oui
	Profondeur de couleurs	16 bit
	Quantité	1 pc(s)
	Résolution maximale	4096 x 2160 Pixels
	Résolutions graphiques prises en charge	4096 x 2160
	Taille des fils AWG	28
	Taux de d'actualisation maximal	60 Hz
	Taux de transfert des données	18 Gbit/s
	Technologie HDR (plage dynamique élevée)	High Dynamic Range 10 (HDR10)
	Technologies Dolby	DTS-HD Master Audio
	Version HDCP	2.2
	Version HDMI	2.0
	Operational conditions	Température d'opération
Package dimensions (verified)	Depth Verified	14,9 cm
	Gross Weight Verified	0,196 kg
	Height Verified	4,9 cm
	Width Verified	16,5 cm
Product dimensions	Net Weight (Product, kg)	0,19 kg
Vendor information	Brand Name	Vivolink
	Warranty	12 Année (s)
Weight & dimensions	Diamètre du câble	7,3 mm

Autres produits de cette série



Longueur de câble	Blanc	Noir
0.25 m		PROHDMIHD0.25
0.5 m	PROHDMIHD0.5W	PROHDMIHD0.5
1.0 m	PROHDMIHD1W	PROHDMIHD1
1.5 m	PROHDMIHD1.5W	PROHDMIHD1.5
2.0 m	PROHDMIHD2W	PROHDMIHD2
3.0 m	PROHDMIHD3W	PROHDMIHD3
5.0 m	PROHDMIHD5W	PROHDMIHD5
7.5 m	PROHDMIHD7.5W	PROHDMIHD7.5
10.0 m	PROHDMIHD10W	PROHDMIHD10
12.5 m		PROHDMIHD12.5
15.0 m	PROHDMIHD15W	PROHDMIHD15-18G
20.0 m	PROHDMIHD20W	PROHDMIHD20-18G

Accessoires recommandés



Vivolink Pro HDMI to DP Adapter Ring
MPN: PROADRING1



Vivolink Pro HDMI Adapter Ring
MPN: PROADRING2