



X-Pro USB 3.2 Gen 2x2 Portable SSD



High Speed File Transfer

Read speeds up to 1,600 MB/s* and write speeds up to 1,500 MB/s*



Ultra-Compact Form Factor

Durable, ultra-compact aluminum housing



USB 3.2 Gen 2x2

USB 3.2 Gen 2x2 connectivity backward compatible with USB 3.2 Gen 2x1, USB 3.2 Gen 1, USB 2.0 and USB 1.1

X-PRO PORTABLE SSD

The X-Pro USB 3.2 Gen 2x2 Type-C Portable SSD is the next generation in mobile storage, boasting not only increased storage capacity, but also exceptional performance, with a USB 3.2 Gen 2x2 interface and read and write speeds up to 1,600 MB/s and 1,500 MB/s respectively*. It's designed to be a mobile storage solution superior to previous generations of portable SSD's, as well as traditional USB 3.0 flash drives, allowing for even faster transfer and storage of files on the go.

The X-Pro USB 3.2 Gen 2x2 Type-C Portable SSD allows for expanded connectivity. Access your data anytime, anywhere, from a vast array of host devices, both USB-A and USB-C enabled. It comes with both a USB Type-C to C cable and a USB Type-C to A cable, right in the box. What's more, the included Acronis True Image Data Protection Software easily backs up data.

The X-Pro USB 3.2 Gen 2x2 Type-C Portable SSD features a sleek, aluminum design that fits comfortably in the palm of your hand, making it the perfect solution for life on the go.

FEATURES AND BENEFITS

- Performance of up to 1,600 MB/s seq. read and 1,500 MB/s seq. write*
- Durable, ultra-compact aluminum housing
- Low power consumption
- USB 3.2 Gen 2x2 connectivity, backwards compatible with USB 3.1 Gen2x1, USB 3.1 Gen1, USB 2.0 and USB 1.1
- · Compatible with Windows, Mac OS X and Linux kernel

PRODUCT SPECIFICATIONS

Interface	USB 3.2 Gen 2x2; Backwards compatible with USB 3.2 Gen 2x1, USB 3.2 Gen 1, USB 2.0 and USB 1.1
Form Factor	Portable
PERFORMANCE (MAX SEQUENT	TIAL READ/WRITE)
500GB	1,500 MB/s (Read) 900 MB/s (Write)
1TB	1,500 MB/s (Read) 1,400 MB/s (Write)
2TB	1,600 MB/s (Read) 1,500 MB/s (Write)
4TB	1,600 MB/s (Read) 1,500 MB/s (Write)
ENVIRONMENTAL	
Operating Temperature	0°C ~ 70°C
Storage Temperature	-40°C ~ 85°C
Certifications	CE, FCC, EMC, ROHS, REACH, UKCA
COMPATIBILITY	
Operating Systems	Windows 11, Windows 10, Windows 8, Windows 7, Windows Vista™, Windows XP™, Mac OS X, Linux kernel 2.4.10
ADDITIONAL FEATURES	
Service & Support	3-Year Limited Warranty or TBW**
PRODUCT INFORMATION	
Usable Capacities (IDEMA)	500GB, 1TB, 2TB, 4TB
PNY Part Number	500GB: PSD0CS2260-500-RB 1TB: PSD0CS2260-1TB-RB 2TB: PSD0CS2260-2TB-RB 4TB: PSD0CS2260-4TB-RB
Package Dimensions	3.94" x 5.13" x 1.26"
Dimensions (L x W x H)	2.50" x 2.25" x 0.43"

*Sequential read and write data transfer rates based on PNY internal testing.

Performance may differ depending upon host device

**For full details visit www.pny.com