

4 Port Black SuperSpeed USB 3.0 Hub

Product ID: ST4300USB3EU



The ST4300USB3EU 4-Port SuperSpeed USB 3.0 Hub allows you to add 4 additional USB 3.0 ports from a single USB 3.0 connection to the host computer system.

Backward compatible with USB 2.0 and USB 1.x standards, this USB 3.0 hub still supports older USB devices and can also be used as a hub on older systems that do not have USB 3.0 ports.

With the capability to mix and match USB 3.0/2.0/1.x devices and be used with or without the included external power adapter, this hub offers the best of versatility and portability.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Expand your USB 3.0 capabilities with additional ports
- Make hard to access USB ports more accessible by being able to position the hub anywhere the cable will reach
- Extend the range of a USB device by having the hub act as a mid-point repeater

Features

- Four USB type 'A' ports that can each be accessed simultaneously
- SuperSpeed USB 3.0 compliant, with data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.0/1.1 devices
- Supports USB 3.0/2.0/1.x devices simultaneously at full bandwidth
- Provides up to 900mA of power per port
- Compact, desktop-style form factor
- Plug-and-Play and hot-swap compatible

| | | |
|-------------------------------------|-------------------------------|--|
| Hardware | Warranty | 2 Years |
| | Chipset ID | VIA/VLI - VL811+ |
| | Fast-Charge Port(s) | No |
| | Interface | USB 3.0 |
| | Ports | 4 |
| | USB-C Device Port(s) | No |
| | USB-C Host Connection | No |
| Performance | Maximum Data Transfer Rate | 5 Gbps |
| Connector(s) | External Ports | 1 - USB Type-B (9 pin) USB 3.0 Female 4 - USB Type-A (9 pin) USB 3.0 Female |
| | | |
| Software | OS Compatibility | OS Independent; No additional drivers or software required |
| Special Notes / Requirements | Note | If used with the Apple Mac OS operating system, this device will function in USB 2.0 mode only |
| | System and Cable Requirements | USB 3.0 or 2.0 or 1.x compliant host controller with available port. |
| Indicators | LED Indicators | 1 - Power (Blue) |
| Power | Center Tip Polarity | Positive |
| | Input Voltage | 110V-240V AC |
| | Output Current | 2A |
| | Output Voltage | 5 DC |
| | Plug Type | M |
| | Power Consumption (In Watts) | 10 |
| | Power Source | AC Adapter Included |
| Environmental | Humidity | 5~85% RH |
| | Operating Temperature | 0°C to 50°C (32°F to 122°F) |
| | Storage Temperature | -20°C to 60°C (-4°F to 140°F) |
| Physical Characteristics | Color | Black |
| | Enclosure Type | Plastic |
| | Form Factor | Desktop |
| | Product Height | 23 mm [0.9 in] |
| | Product Length | 95 mm [3.7 in] |
| | Product Weight | 55 g [1.9 oz] |

| | | |
|------------------------------|---------------------------|---|
| | Product Width | 68 mm [2.7 in] |
| Packaging Information | Shipping (Package) Weight | 0.4 kg [1 lb] |
| What's in the Box | Included in Package | 1 - USB 3.0 Hub 1 - USB 3.0 cable 1 - Power Adapter 1 - Instruction Manual |

Product appearance and specifications are subject to change without notice.