



3.5 HDD DATA SHEET

Amazing Versatility. Unmatched Dependability.

Seagate brings over 20 years of trusted performance and reliability to the Seagate[®] BarraCuda[®] 3.5-inch HDD—now available in capacities up to 8TB.





Best-Fit Applications

- Desktop or all-in-one PCs
- Home servers
- Entry-level direct-attached storage devices (DAS)

Key Advantages

Versatile HDDs for all your PC needs bring you industry-leading excellence in personal computing.

For over 20 years the BarraCuda family has delivered super-reliable storage for the hard drive industry.

Capacities up to 8TB for desktops, BarraCuda leads the market with the widest range of storage options available.

Advanced Power modes help save energy without sacrificing performance.1

SATA 6Gb/s interface optimizes burst performance.1

Seagate Secure®models provide Self-Encrypting Drive (SED) hardware-based data security and deliver an Instant Secure Erase feature for safe, fast and easy drive retirement. They meet NIST 800-88 media sanitization specifications and also support the Trusted Computer Group (TCG) Opal standard.^{2,3}

¹ Performance may vary depending on user's hardware configuration and operating system.

 $^{2\,}Seagate\,Secure\,models\,are\,not\,available\,in\,all\,\,countries.\,May\,\,require\,TCG-compliant\,host\,or\,\,controller\,\,support.$

³ Refer to specifications table for further information and feature options.





Specifications	8TB	6TB	4TB	3ТВ	3ТВ	
Standard Model Numbers	ST8000DM004	ST6000DM003	ST4000DM004	ST3000DM007	ST3000DM008	
Seagate Secure® Model Numbers	_	_	_	_	ST3000DM002	
Bytes per Sector	4096	4096	4096	4096	4096	
Heads/Disks	8/4	6/3	4/2	3/2	6/3	
Performance						
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	
Max. Sustained Transfer Rate OD (MB/s)	190MB/s	185MB/s	190MB/s	185MB/s	210MB/s	
Cache, Multisegmented (MB)	256	256	256	256	64	
Reliability/Data Integrity	eliability/Data Integrity					
Load/Unload Cycles	300,000	300,000	300,000	300,000	300,000	
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	
Power-On Hours per Year (24×7)	2,400	2,400	2,400	2,400	2,400	
Workload Rate Limit (TB/Year)	55	55	55	55	55	
Limited Warranty (years)	2	2	2	2	2	
Power Management						
Startup Power (A)	2	2	2	2	2.5	
Operating Mode, Typical (W)	5.3	5.3	3.7	3.7	8	
Idle Average (W)	3.4W	3.4W	2.5W	2.5W	5.4W	
Standby Mode/Sleep Mode, Typical (W)	0.25/0.25	0.25/0.25	0.25/0.25	0.25/0.25	0.75/0.75	
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%	±5%	±5%	
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%	±10%	±10%	
Environmental/Temperature						
Operating (ambient, min)	0°C	0°C	0°C	0°C	0°C	
Operating (drive case, max)	60°C	60°C	60°C	60°C	60°C	
Nonoperating (ambient)	-40°C – 70°C	-40°C – 70°C	-40°C – 70°C	-40°C – 70°C	-40°C – 70°C	
Halogen Free	Yes	Yes	Yes	Yes	Yes	
RoHS Compliance	Yes	Yes	Yes	Yes	Yes	
Physical						
Height (mm/in, max)	26.11mm/1.028in	26.11mm/1.028in	20.2mm/0.795in	20.2mm/0.795in	26.11mm/1.028in	
Width (mm/in, max)	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	
Weight (g/lb)	630g/1.389lb	610g/1.345lb	490g/1.08lb	490g/1.08lb	626g/1.38lb	
Carton Unit Quantity	20	20	25	25	20	
Cartons per Pallet/Cartons per Layer	40 / 8	40 / 8	40 / 8	40 / 8	40 / 8	





Specifications	2TB	1TB	500GB			
Standard Model Numbers	ST2000DM006	ST1000DM010	ST500DM009			
Seagate Secure® Model Numbers	ST2000DM002	_	_			
Bytes per Sector	4096	4096	4096			
Heads/Disks	6/3 or 4/2	2/1	2/1			
Performance						
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s			
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5			
Max. Sustained Transfer Rate OD (MB/s)	210MB/s	210MB/s	210MB/s			
Cache, Multisegmented (MB)	64	64	32			
Reliability/Data Integrity						
Load/Unload Cycles	300,000	_	_			
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14			
Power-On Hours per Year (24×7)	2,400	2,400	2,400			
Workload Rate Limit (TB/Year)	55	55	55			
Limited Warranty (years)	2	2	2			
Power Management						
Startup Power (A)	2.5	2	2			
Operating Mode, Typical (W)	8	5.3	5.3			
Idle Average (W)	5.4W	4.6W	4.6W			
Standby Mode/Sleep Mode, Typical (W)	0.75/0.75	0.94/0.94	0.94/0.94			
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%			
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%			
Environmental/Temperature						
Operating (ambient, min)	0°C	0°C	0°C			
Operating (drive case, max)	60°C	60°C	60°C			
Nonoperating (ambient)	-40°C – 70°C	-40°C - 70°C	-40°C – 70°C			
Halogen Free	Yes	Yes	Yes			
RoHS Compliance	Yes	Yes	Yes			
Physical						
Height (mm/in, max)	26.11mm/1.028in	19.99mm/0.787in	19.99mm/0.787in			
Width (mm/in, max)	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in			
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in			
Weight (g/lb)	626g/1.38lb	400g/0.88lb	400g/0.88lb			
Carton Unit Quantity	20	25	25			
Cartons per Pallet/Cartons per Layer	40 / 8	40 / 8	40 / 8			



AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2017 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. BarraCuda and Seagate Secure are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1900.9-1710US October 2017