

MPN: MC-USB3.0-ST610

PCIe x1 VL805+VL812 USB3.0 (5+2)-Port Card

This product is a single-chip USB 3.0 Host controller that allows a PCI Express platform to connect with USB devices at Super-Speed (5Gbps), High-Speed (480Mbps), Full-Speed (12Mbps), and Low-Speed (1.5Mbps). It supports easy connection of mass storage, printers, scanners, hubs, cameras, and other USB devices.

Linux, Win7/Win8/Win8.1/Win10 32bit or 64 bit

- Compliant with PCI Express base specification 2.0 backward with PCI Express 1.0
- Compliant to Universal Serial Bus 3.0 Specification Revision 1.0
- Compliant to Universal Serial Bus 2.0 Specifications
- Compliant to eXtensible Host Controller Interface Specification Revision 1.0
- Support 4 Ports USB3.0 Type AF
- Support Legacy USB Function, Four Down-stream ports Support Super-Speed (5Gbps)High-Speed(480Mbps),Full-Speed(12Mbps) and Low-Speed (1.5Mbps)
- USB Attached SCSI Protocol(UASP)mode
- Max. 5V/900mA power output to each USB 3.0 Port
- 15pin SATA Power connector for extra power
- Fully plug ,play and hot plug compatible



Caractéristiques

Design	Interne	Oui
Features	Bande passante	5 Gbit/s
Operational conditions	Température d'opération	5 - 35 °C
Package dimensions	Depth (package,cm)	13 cm
	Gross Weight (Package, kg)	0,09 kg
	Height (package,cm)	3,4 cm
	Width (package,cm)	17,4 cm
Packaging data	Drivers inclus	Oui
	Quantité	1
Ports & interfaces	Interface de l'hôte	PCIe
	Interface de sortie	Thunderbolt 3
	Quantité de ports de type A USB 3.2 Gen 1 (3.1 Gen 1)	7
	Quantité de ports internes USB 3.2 Gen 1 (3.1 Gen 1)	1
Product dimensions	Net Weight (Product, kg)	0,09 kg
	Product Depth	7 cm
	Product Width	8 cm
System requirements	Prise en charge du système	Oui

System requirements	d'exploitation Windows	Oui
Vendor information	Brand Name	MicroConnect
	Warranty	3 Année (s)